

# Triumph®

## PAPER CUTTERS

### ➔ 4850 EP AUTOMATIC PROGRAMMABLE CUTTER

"SCS" (Safety Cutting System) package: transparent, electronically controlled front safety guard; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | high storage capacity, programmable "EP" back gauge control module with 10 button keypad and LED display stores 99 programs (up to 99 steps each) and frequently used measurements | up to 9 repeat cuts can be integrated into a program in a single step | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut and eject functions | "set" function key for reference measurement | self-diagnostic system with error indication on display | electric blade, clamp, and back gauge drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | automatic clamp is guided on both sides to apply even pressure along entire cutting width (can be lowered or raised independently from blade) | dual side guides on front and rear tables | spindle-guided back gauge with narrow separations and plastic gliders | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | all-metal construction | stand with storage shelf

Dimensions (D x W x H): 38 1/4 x 29 3/4 x 48 1/2 inches, Shipping weight: 556 lbs.




#### "EP" CONTROL MODULE



The "EP" back gauge control module stores 99 programs and frequently used measurements.

#### OPTICAL CUTTING LINE



An optical cutting line indicates exact location of cut and helps to perfectly position trim marks.

#### AUTOMATIC CLAMP CONTROL



The automatic clamp control allows clamp to be moved up or down, independent of blade.

#### ➔ TRIUMPH 4850 EP

Cutting width	18 5/8"
Cutting height	3"
Narrow cut	1 3/8"
Cutting length behind blade	17 1/16"
Table length in front of blade	13 5/8"
Motor	2 hp
Power supply	115 V, 60 Hz*

\* 20 amp dedicated line required