

# Triumph®

## PAPER CUTTERS

### ➔ 5222 DIGICUT PROGRAMMABLE HYDRAULIC CUTTER

"SCS" (Safety Cutting System) package: front safety light beams; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | high storage capacity, programmable "EP" back gauge control module with 10 button keypad and LED display stores 99 programs (up to 99 steps each) and frequently used measurements | up to 9 repeat cuts can be integrated into a program in a single step | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut and eject functions | "set" function key for reference measurement | self-diagnostic system with error indication on display | electric blade and back gauge drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | hydraulic clamp drive | clamp is guided on both sides to apply even pressure along entire cutting width and is fully adjustable between 440 and 2,420 psi (ideal for digital printing) | false clamp and foot pedal for pre-clamping | dual side guides on front and rear tables | electric, spindle-guided back gauge with narrow separations and plastic gliders | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | standard side tables extend work area | all-metal construction

Dimensions (D x W x H): 43 x 65 x 51 1/2 inches, Shipping weight: 900 lbs.



#### "EP" CONTROL MODULE



The "EP" back gauge control module stores 99 programs and frequently used measurements.

#### SAFETY LIGHT BEAMS



Safety light beams protect the operator and allow back gauge to automatically advance to the next cut.

#### ➔ TRIUMPH 5222 DIGICUT

|                                |                |
|--------------------------------|----------------|
| Cutting width                  | 20 1/2"        |
| Cutting height                 | 3 1/8"         |
| Narrow cut                     | 7/8"*          |
| Cutting length behind blade    | 20 3/8"        |
| Table length in front of blade | 16"            |
| Motor                          | 2 hp           |
| Power supply                   | 115 V, 60 Hz** |

\* 3 1/2" with false clamp

\*\* 20 amp dedicated line required